


Part Number: 2402POHPL-E00
Description: 2 x 2 x 24(7)AWG Two Pair Foil & Braid Screened LSF Data Cable



Construction

Conductor Material	: Tinned Copper, 24(7)awg
Insulation Material	: Polyethylene (PE)
Number of Pairs	: 2
Overall Screen 1	: Aluminium Foil (100% Coverage)
Drain Wire	: Tinned Copper, 24(7)awg
Overall Screen 2	: Tinned Copper Wire Braid (90% Coverage)
Outer Sheath Material	: Low Smoke & Fume (LSF)
Outer Sheath Colour	: Grey
Core Identification	: White/Blue Stripe, Blue/White Stripe White/Orange Stripe, Orange/White Stripe
Alternative to Belden	: 9842

Electrical Characteristics

Nominal Conductor Resistance	: < 86.2 Ω /km
Insulation Resistance	: > 200M Ω .M
Impedance	: 120 Ohm \pm 25
Capacitance	Core to Core : 42 pF/m \pm 20
	Core to Screen : 76 pF/m \pm 35
Voltage Rating	: 450/750V <i>Applies to CE marked FSC branded stock only</i>
Test Voltage	: 2.5kV for 5 minutes

Physical Characteristics

Overall Diameter	: 8.7 \pm 0.2mm
Min. Bend Radius	: 10 x OD
Temperature Rating	: -20°C to +70°C
Weight	: 95 kg/km

Standards

Flame Retardant	: BS EN 60332-1-2
RoHS3 Compliant	: Yes
CE Compliant	: LVD (2014/35/EU), CPR (305/2011)
CPR Classification	: Eca (EN50575:2014+A1:2016)